

TRANSPORTATION IMPACT EMERALD ISLE, NORTH CAROLINA

BLIRKE DESIGN GROUP, PA
3305-109 DURHAM DRIVE
RALEIGH, NC 27603
PHONE: (919) 771-1916
FAX: (919) 779-0826
email: benburke@nc.rr.com
Corp. License # C-2652



FIXTURE SCHEDULE - PLUMBING *

- SP-1 * ELEVATOR SUMP PUMP
STANCOR MODEL SB-12 MULTI-OPTION ELEVATOR OIL MINDER SYSTEM. 1/6 HP, 115 V, 2.1 A, 1 PH, 25' MAX HEAD. HT. 1" DISCHARGE CONNECTION. INCLUDES REMOTE ALARM-VERIFY LOCATION. VERIFY MIN. PIT SIZE REQUIREMENTS.
- SP-2 * ELEVATOR SUMP PUMP
STANCOR MODEL SB-12 MULTI-OPTION ELEVATOR OIL MINDER SYSTEM. 1/6 HP, 115 V, 2.1 A, 1 PH, 25' MAX HEAD. HT. 1" DISCHARGE CONNECTION. INCLUDES REMOTE ALARM-VERIFY LOCATION. VERIFY MIN. PIT SIZE REQUIREMENTS.
- WC1 * LOW-FLOW WATER CLOSET (ADA FLUSH TANK)
ADA COMPLIANT 1.0-1.1 GPF. PROVIDE ADA SEAT, SUPPLY AND STOP, WAX SEAL, CLOSET BOLT KIT. PROVIDE MODEL WITH FLUSH CONTROL ON SIDE OPPOSITE GRAB BAR. PRESSURE ASSISTED VALVE MAY BE REQUIRED. VERIFY SUPPLY (PSI) REQUIREMENTS. COORDINATE MODEL W/OWNER.
- WC2 * LOW-FLOW WATER CLOSET (FLUSH TANK)
1.0-1.1 GPF. PROVIDE SEAT, SUPPLY AND STOP, WAX SEAL, CLOSET BOLT KIT. PROVIDE MODEL WITH FLUSH CONTROL ON SIDE OPPOSITE GRAB BAR. PRESSURE ASSISTED VALVE MAY BE REQUIRED. VERIFY SUPPLY (PSI) REQUIREMENTS. COORDINATE MODEL W/OWNER.
- L1 * LAVATORY (DROP-IN)
KOHLER YN-YANG LAVATORY, K-2354-1, VITREOUS CHINA, SINGLE HOLE, ADA COMPLIANT. PROVIDE KOHLER FAUCET K-14402, POLISHED CHROME FINISH. PROVIDE P-TRAP, SHUT-OFF VALVES. COORDINATE EXACT UNIT WITH OWNER AND G.C. COORDINATE SIZE WITH CABINETS PRIOR TO ORDERING.
- L2 * LAVATORY (WALL MOUNT)
PROVIDE LAV/FAUCET (ADA MODEL IF REQUIRED), P-TRAP, AND SHUT-OFF VALVES. PROVIDE FAUCET MODEL WITH 0.5 GPM FLOWRATE. COORDINATE LAV/FAUCET MODEL W/OWNER.
- L3 * LAVATORY (COUNTERTOP)
PROVIDE LAV/FAUCET (ADA MODEL IF REQUIRED), P-TRAP, AND SHUT-OFF VALVES. PROVIDE FAUCET MODEL WITH 0.5 GPM FLOWRATE. COORDINATE LAV/FAUCET MODEL W/OWNER.
- L4 * LAVATORY (DROP-IN)
KOHLER YN-YANG LAVATORY, K-2354-1, VITREOUS CHINA, SINGLE HOLE, ADA COMPLIANT. POLISHED CHROME FINISH. PROVIDE SLOAN OPTIMA #EBF-615 BATTERY OPERATED SENSOR FAUCET, P-TRAP, SHUT-OFF VALVES. COORDINATE EXACT UNIT WITH OWNER AND G.C. COORDINATE SIZE WITH CABINETS PRIOR TO ORDERING.
- L5 * LAVATORY (COUNTERTOP)
PROVIDE LAV/FAUCET (ADA MODEL IF REQUIRED), P-TRAP, AND SHUT-OFF VALVES. PROVIDE FAUCET MODEL WITH 0.5 GPM FLOWRATE. COORDINATE LAV/FAUCET MODEL W/OWNER.
- SH1 * ACCESSIBLE STALL, LOW-FLOW SHOWER HEAD/FAUCET/ADA ACCESSORIES
ADA PRE-FABRICATED FIBERGLASS SHOWER STALL. PROVIDE ADA SHOWER/CONTROLS, ALL OTHER COMPONENTS REQUIRED FOR ADA COMPLIANCE. GRAB BAR, SEAT, CURTAIN OR DOOR, ETC. COORDINATE HANDING WITH OWNER AND ROUTE PLUMBING AS REQUIRED. COORDINATE MODEL W/OWNER. PROVIDE STANDARD MODEL IF ADA NOT REQUIRED. PROVIDE SHOWER HEAD MODEL WITH 0.5-1.5 GPM FLOWRATE.
- SH2 * ACCESSIBLE LOW-FLOW SHOWER HEAD/FAUCET/ADA ACCESSORIES
PROVIDE ADA SHOWER/CONTROLS, ALL OTHER COMPONENTS REQUIRED FOR ADA COMPLIANCE. GRAB BAR, SEAT, CURTAIN OR DOOR, ETC. COORDINATE HANDING WITH OWNER AND ROUTE PLUMBING AS REQUIRED. COORDINATE MODEL W/OWNER. PROVIDE STANDARD MODEL IF ADA NOT REQUIRED. PROVIDE SHOWER HEAD MODEL WITH 0.5-1.5 GPM FLOWRATE.
- SH3 * ACCESSIBLE LOW-FLOW SHOWER HEAD/FAUCET/ADA ACCESSORIES
PROVIDE ADA SHOWER/CONTROLS, ALL OTHER COMPONENTS REQUIRED FOR ADA COMPLIANCE. GRAB BAR, SEAT, CURTAIN OR DOOR, ETC. COORDINATE HANDING WITH OWNER AND ROUTE PLUMBING AS REQUIRED. COORDINATE MODEL W/OWNER. PROVIDE STANDARD MODEL IF ADA NOT REQUIRED. PROVIDE SHOWER HEAD MODEL WITH 0.5-1.5 GPM FLOWRATE.
- DF * DRINKING FOUNTAIN
HALSEY TAYLOR BARRIER FREE DRINKING FOUNTAIN MODEL #OVL-II SEBP, ADA COMPLIANT. INSTALL PER MFR'S SPECIFICATIONS. PIPE TO SINGLE DRAIN AND SUPPLY LINE.
- S1 * WET BAR SINK
SINGLE BASIN STAINLESS STEEL (VERIFY) SINK (PROVIDE ADA MODEL IF REQUIRED) WITH FAUCET, CHROME PLATED BRASS P-TRAP AND SHUT-OFF VALVES. COORDINATE EXACT UNIT WITH OWNER AND GENERAL CONTRACTOR. COORDINATE SIZE WITH CABINETS PRIOR TO ORDERING. COORDINATE SINK/FAUCET MODEL W/OWNER. PROVIDE FAUCET MODEL WITH 0.5 GPM FLOWRATE.
- S2 * BREAK ROOM SINK
DOUBLE BASIN STAINLESS STEEL SINK (PROVIDE ADA MODEL IF REQUIRED) WITH FAUCET, CHROME PLATED BRASS P-TRAP AND SHUT-OFF VALVES. COORDINATE EXACT UNIT WITH OWNER AND GENERAL CONTRACTOR. COORDINATE SIZE WITH CABINETS PRIOR TO ORDERING. COORDINATE MODEL W/OWNER.
- S3 * KITCHEN SINK
DOUBLE BASIN STAINLESS STEEL (VERIFY) SINK (PROVIDE ADA MODEL IF REQUIRED) WITH FAUCET, CHROME PLATED BRASS P-TRAP AND SHUT-OFF VALVES. COORDINATE EXACT UNIT WITH OWNER AND GENERAL CONTRACTOR. COORDINATE SIZE WITH CABINETS PRIOR TO ORDERING. COORDINATE SINK/FAUCET MODEL W/OWNER. PROVIDE FAUCET MODEL WITH 0.5 GPM FLOWRATE.
- WB * WASHING MACHINE WALL BOX
SUPPLY AND DRAIN FIXTURE: POLYSTYRENE BOX WITH 2" DRAIN, 1/4 TURN BRASS BALL VALVES. OATEY OR APPROVED EQUAL.
- VB * ICE MAKER VALVE BOX
OATEY VALVE BOX WITH 3/8" BRONZE SHUT-OFF VALVE. FLUSH TO WALL.

* OR APPROVED EQUAL. SUBMIT ALL ITEMS FOR APPROVAL BY TENANT AND ARCHITECT PRIOR TO ORDERING.
ALL OTHER PLUMBING FIXTURES SHOWN ARE PROVIDED BY THE TENANT AND INSTALLED BY THE PLUMBING CONTRACTOR. SEE PLANS FOR NUMBER AND LOCATION. COORDINATE ALL REQUIREMENTS WITH EQUIPMENT SERVED.

